


LATCHING STYLES

SENTRY I



3-POINT, 3-SIDED TURN HANDLE

- Three sides of pry and vandal resistance.
- Fully welded assembly.
- 3/8" diameter steel rods engage the top and bottom of the frame.
- Accepts padlock or built-in deadbolt.
- Complies with all current ADA standards.

SENTRY II



MULTIPOINT GRAVITY LIFT

- Easy-to-use, slammable latch system.
- Durable nylon clips secure the door to the frame in multiple places, reducing noise.
- Accepts padlock, built-in deadbolt, or springbolt locks.
- Complies with all current ADA standards.

SENTRY III



SINGLE POINT, NON-MOVING

- Durable 11-gauge hasp.
- A quiet, maintenance-free latching system with no moving parts.
- Accepts padlock, built-in springbolt or deadbolt locks.
- Complies with all current ADA standards.

5-KNUCKLE WELDED HINGE



- 14-gauge.
- Welded to the door and the frame.
- Heavy-duty fast pin construction.

CONTINUOUS PIANO HINGE



- 16-gauge.
- Welded to door and riveted to the frame every 6-inches.

BOX LOCKER SIDE HINGE



- 3/16" hinge pin.
- Welded to door.
- Anchored into brass bushings.

BOX LOCKER TOP PIANO HINGE



- 3/16" hinge pin.
- Welded to door.
- Anchored into brass bushings.

OPTIONS

HINGES



FORMED DOOR VENTILATION

ANGLE IRON DOOR VENTILATION



SOLID
0% VENTILATION*



LOUVERED
7% VENTILATION*



DIAMOND PERFORATED
37% VENTILATION*



SECUR-N-VENT
21% VENTILATION*

2b-2cm



SOLID
0% VENTILATION*



LOUVERED
7% VENTILATION*



DIAMOND PERFORATED
37% VENTILATION*



EXPANDED METAL
73% VENTILATION*



SECUR-N-VENT
21% VENTILATION*

VENTILATION CALCULATIONS ARE BASED ON THE VENTILATION AMOUNT PER ONE SQUARE INCH OF THE VENTILATED AREA.